

Asphalt In A Bag

Asphalt In A Bag is a ready to use permanent repair solution for roads, car parks and footpaths. Manufactured from a mix of select aggregates, bitumen and a co-polymer, creating a tenacious bonding material for permanent use and repair.

Asphalt In A Bag is an all weather road repair solution, it's ability to expand and contract with a roads surface ensures a permanent fixture. It can be applied at -26 degrees Celsius and will perform equally well during hot and rainy days at temperatures reaching 49 degrees Celsius.

Curing is activated by impact and it will bond to asphalt, concrete, steel and wood.

No pre-coating or tack coating is required, and as an all weather permanent repair solution it can be used in wet areas such as potholes full of water.

Asphalt In A Bag, when applied according to manufacturers specifications, is guaranteed to adhere permanently to the repair or until the surrounding area fails.

Available in convenient 20 kg bag's, one bag will cover approximately a ½ square metre at a compacted thickness of 22mm. It is also available in 7, 10 and 14 gauge aggregates to cater for different road grades throughout Australia.

The advanced technology of Asphalt In A Bag negates the need for a summer and winter mix to meet extreme Australian conditions, it also allows for extended storage periods in both a bagged or unbagged state.

APPLICATION PROCEDURE

- 1) Remove all loose debris from the pothole where possible.
- 2) With a shovel, apply the mix directly into the hole or pour directly from the bag in layers of 20mm to a level of approximately 5mm above surround.
- 3) For best results, tamp or roll the mix into the newly repaired area.

FILL, COMPACT, USE IMMEDIATELY - - - - - THAT EASY !



HIGH PERFORMANCE POTHOLE PATCH

L R Technologies

4 St James Place, Seven Hills NSW 2147

Ph: 02 9674 6741 Fax: 02 9624 1904 Email: sales@lrtechnologies.com.au

www.lrtechnologies.com.au

